





SPECIFICATIONS		1978 VW BUS
ENGINE	Туре	Air-cooled, rear mounted
	No. of cylinders	Four, horizontally opposed, overhead valves
	Bore & stroke	94 mm x 71 mm, 3.70 in x 2.79 in
	Displacement	1970 cc, 120.2 cu in
	SAE net hp @ rpm	67 @ 4200 rpm
	SAE net torque	101.0 ft lbs @ 3000 rpm
	Compression ratio	7.3:1
	Fuel system	A.F.C. fuel injection (air flow controlled)
	Fuel requirement	Regular gasoline
	Fuel capacity	56/, 12.3 imp gal
	Oil capacity	3.5/, 3.1 imp qts
	Battery	12V/63 Amp/h
	Alternator	70 Amp
	Type of Ignition	Coil, distributor
DRIVE TRAIN	Туре	Rear wheel drive, with two constant velocity joints per drive shaft
	Clutch	Dry, single plate
	Transmission	Fully synchronized four-speed
	Automatic	Three-speed automatic transmission with torque converter
	Gear Ratios	(manual) 3.78/2.06/1.26/0.82/R. 3.28 (auto.) 2.55/1.45/1.00/R. 2.46
	Final Drive	(manual) 4.57 (automatic) 4.09
CHASSIS	Body	Unitized body, frame plates reinforced with side and cross members, front axle bolted to frame side members
	Front suspension	Torsion arms with ball joints, torsion springs and stabilizer
	Rear suspension	Double jointed axle with trailing arms and diagonal links, torsion bars
	Braking system	Power assisted and pressure regulated disc brakes at front, drum brakes ar rear, dual circuit braking system
	Parking brake	Mechanical, effective on rear wheels
	Rim size	51/2 J x 14
	Tire type/size	Steel belted radial tires 185 SR 14
	Steering system	Roller type with maintenance-free tie rods and hydraulic steering damper
	Turning circle	Appr. 11.30 m, 37.1 ft (curb to curb)
	Curb weight	Appr. 1380 kg, 3045 lbs
	Permissible trailer weights	Braked: 1200 kg, 2645 lbs Unbraked: 600 kg, 1323 lbs Trailer tongue load: 50 kg, 110 lbs
FUEL ECONOMY AND PERFORMANCE	Fuel Manual Economy* Automatic	Hwy. 48 km/gal 30 mpg City 34 km/gal 21 mpg Comb. 39 km/gal 24 mpg Hwy. 42 km/gal 26 mpg City 33 km/gal 20 mpg Comb. 36 km/gal 23 mpg
	Top Manual Speed Automatic	127 km/h 79 mph 122 km/h 76 mph
	Accel- Manual eration Automatic	0-80 km/h 50 mph 13.9 sec. 0-80 km/h 50 mph 16.0 sec.

^{*}Results obtained using Transport Canada approved test methods, using standard transmission. Fuel consumption will vary depending on how and where you drive, optional equipment and condition of your car.

Standard features and equipment at no extra charge

- Four-wheel independent suspension
- Front stabilizer
- Steel belted radial tires
- Power assisted brakes
- Front vent windows
- Dual outside mirrors
- Padded dashboard
- Electric fresh air ventilation
- Auxiliary heater
- Day/night inside rear view mirror
- Walk-through aisle
- Sliding side door
- Carpeted luggage area
- Rear window defogger

1978 Colours

Paint









Panama Brown Agate Brown Reef Blue

Sage Green

Interior leatherette





Canyon Brown





Canyon Brown

Alabaster

Alabaster

(Dakota Beige above belt line) (Pastel White above belt line)