

**CARRY
MORE
ECONOMICALLY.**



**BUY A VW
DIESEL PICK-UP.**



TECHNICAL DATA

ENGINE

Location	rear
Number of cylinders	4
Cylinder layout	in line
Displacement	1588 cc
Compression ratio	23.5:1
Maximum output DIN	50 hp at 4500 rpm
SAE	60 hp at 4900 rpm
Maximum torque DIN	9.5 mkg at 3000 rpm
SAE	10.4 mkg at 3400 rpm
Cooling	by water
Fuel feed	injector pump, Bosch VE rotary type

TRANSMISSION

Drive	rear wheel
Gearbox	mechanical, 4 synchronized front speeds and 1 reverse gear
Gear ratio	
1st gear	1:3.80
2nd gear	1:2.06
3rd gear	1:1.32
4th gear	1:0.88
reverse gear	1:3.88
Differential ratio	1:5.143

PERFORMANCE

Maximum speed	108 kph
Economical speed	
2nd gear	18 to 33 kph
3rd gear	27 to 51 kph
4th gear	41 to 77 kph

SUSPENSION

Front	2 torsion bars (beams), double-action telescopic shock absorbers and stabilizer
Rear	2 torsion bars (cylindrical) double-action telescopic shock absorbers.

STEERING

Type	roller; hydraulic damper
Turn diameter	12 m
Steering wheel turns from lock to lock	3.5

BRAKES

Footbrake	hydraulic on 4 wheels - drums at front and rear, brake servo
Handbrake	mechanical, acting on rear wheels

WHEELS

Tyres	7.35 x 14 8 PR
Rims	5 1/2 J x 14 H 1 B

DIMENSIONS (mm)

Length	4437
Width	1941
Height	1918
Track - front	1387
- rear	1420
Wheelbase	2400
Ground clearance (with maximum load)	200

WEIGHTS (kg)

Net weight	1305
Payload	1075
Total permissible weight	2380

RE-FILLING CAPACITIES (litres)

Fuel tank	47
Sump	3.0 (3.5 with strainer)
Gearbox/differential	2.0

CARGO DECK (m²)

Area	4.9
------------	-----

ELECTRICAL SYSTEM

Battery	12V / 54 Ah
Alternator	35 A - 490 W

Technical data subject to alterations without prior notice.



VOLKSWAGEN DO BRASIL S. A.